

## ASM400 型防水栓工作站

ASM400 SEAL LOADING MACHINE

### 产品介绍 Introduction

ASM400型防水栓穿入单元为全自动线束加工系统提供了强有力的支持，该设备完美匹配HBQ-802型全自动下线压接机，用于将防水栓安装至已剥去绝缘皮导线的末端，具有防水栓自动上料、筛选、送料、扩张、穿入功能，适用于各种防水栓。精密的防水栓定位系统确保了加工的精度，紧凑的外形结构，可靠的监控，使其成为THB全自动压接机的首选配置。

ASM400 Seal Loading Machine provides strong support for automatic wire processing system, which perfectly match to HBQ-802 Fully Automatic Crimping Machine, insert seals to the end of stripped wires. With functions of automatic feeding, filtering, expanding and inserting, applicable to all kinds of seals. Precise positioning system to ensure the accurate processing, mini structure and reliable control, make its become the preferred accessory of THB automatic machine.

### 特性 Features

- 超薄机身设计，减少自动机空间的占用；
  - 多路传感器检测，保证穿入正确性，减少废品的产生；
  - 模块化设计，更换方便；
  - 完美兼容THB自动机。
- The ultra-thin body design, reduce the space occupied by the automaton;
  - The multiple sensor detection to ensure the correctness of penetration, reduce the waste;
  - The modular design, convenient replacement;
  - The perfect and compatible THB automaton.

### 技术参数 Specifications

线外径 Outside diameter	1~5mm
防水栓尺寸 Seal size	Height & Diameter <17mm
加工时间 Processing time	0.22S
机器循环时间 Cycle time	0.9S
电源 Power supply	100~220VAC, 50Hz, 200W
气源 Air supply	5.5~7Bar
包装尺寸 Package dimension	L1000*W800*H350mm
重量 Weight	30Kg

