

S3B型模具

S3BCRIMPING APPLICATOR

产品介绍 Introduction

压接高度连续调节系统：C.H./I.H.调节精度0.02mm，调节范围2.0mm，

调节节奏感强，刻度易识别，满足您对压接质量的“苛刻”要求；

模块化结构：便于调整和维护，超强柔性缔造无限拓展空间，彻底打破端子与压接模具1：1的格局，经济实惠；

送料机构：同时为您提供前送料（半自动）和后送料（全自动）两种解决方案；

送料步距可见。

快换机构：完美匹配Komax、AMP、Mecal等欧美品牌的半自动和全自动压接机；

技术文件：提供完整的使用、保养说明书，如有要求，也可提供机器能力研究、断面分析报告等文件；

QW表面处理：永不锈蚀；

激光打标：每个零件都拥有自己的ID。



• S3B

Continuous crimping height adjustment : Can be supplied either with a continuous or a wedge regulating head,providing a 0.02mm resolution for C.H./I.H.and a 2.0mm range, which satisfied your rigorous demand on the crimping.

Modularized framework: Can be adjusted and maintained conveniently. it drastically breaks the pattern that terminal to applicator for 1:1,.

Feeding mechanism: Terminal pitch 40mm become true easily and feeding speed can be adjusted with facility,can be supplied either with shot stroke cylinder or oriented cylinder for choice, which can enable you to operate the machine freely.

Switch system: Can be fitted to semi-automatic and fully automatic crimping machine for Occident brand such as Komax,AMP,Mecal and so on.

Technical documentation: You can get a complete technical documentation containing all the information needed to safely use and correctly maintain the equipment. Upon request, a capability study& Cross-section Analysis can be provided.

Surface plating: Anti-corrosion

ID: Laser etching ID to each spare parts

技术参数 Specifications

型号	Model	YJM-S300A/E300A/S3B
料带形式	Description	横向/纵向Side Feed /End Feed
闭合高度	Crimping Height	135.8 mm
行程	Stroke	40/30 mm
送料步距	Terminal Pitch	27mm (max)
适应端子料厚	Terminal Thickness	1.2 mm (max)
适应线径	Cross Section	0.08~6mm ²
送料机构	Feeding System	机械 Mechanical
重量	Weight	4 Kg
外形尺寸(mm)	Dimension (mm)	W195×H155×D70